

Section 3: Files, Pipes, Signals, Dup, Synchronization

CS 162

September 18, 2020

Contents

1	Vocabulary	2
2	Files	4
2.1	Files vs File Descriptor	4
2.2	Quick practice with write and seek	4
2.3	Reading and Writing with File Pointers vs. Descriptors	5
3	Pipes	6
3.1	Basic Pipes	6
3.2	Pipe and Fork	7
4	Signals	8
4.1	Signal Handlers	9
5	Dup and Dup2	10
6	Synchronization	11
6.1	Locking via Disabling Interrupts	11

1 Vocabulary

- **file descriptors** - File descriptors are an index into a file-descriptor table stored by the kernel. The kernel creates a file-descriptor in response to an open call and associates the file-descriptor with some abstraction of an underlying file-like object; be that an actual hardware device, or a file-system or something else entirely. Using file descriptors, a process's read or write calls are routed to the correct place by the kernel. When your program starts you have 3 file descriptors.

File Descriptor	File
0	stdin
1	stdout
2	stderr

- **int open(const char *path, int flags)** - open is a system call that is used to open a new file and obtain its file descriptor. Initially the offset is 0.
- **size_t read(int fd, void *buf, size_t count)** - read is a system call used to read `count` bytes of data into a buffer starting from the file offset. The file offset is incremented by the number of bytes read.
- **size_t write(int fd, const void *buf, size_t count)** - write is a system call that is used to write up to `count` bytes of data from a buffer to the file offset position. The file offset is incremented by the number of bytes written.
- **size_t lseek(int fd, off_t offset, int whence)** - lseek is a system call that allows you to move the offset of a file. There are three options for whence
 - SEEK_SET - The offset is set to `offset`.
 - SEEK_CUR - The offset is set to `current_offset + offset`
 - SEEK_END - The offset is set to the size of the file + `offset`
- **test_and_set** - An atomic operation implemented in hardware. Often used to implement locks and other synchronization primitives. In this handout, assume the following implementation.

```
int test_and_set(int *value) {
    int result = *value;
    *value = 1;
    return result;
}
```

This is more expensive than most other instructions, and it is not preferable to repeatedly execute this instruction.

- **pipe** - A system call that can be used for interprocess communication.

More specifically, the `pipe()` syscall creates two file descriptors, which the process can `write()` to and `read()` from. Since these file descriptors are preserved across `fork()` calls, they can be used to implement inter-process communication.

```
/* On error, pipe() returns -1. On success, it returns 0
 * and populates the given array with two file descriptors:
 * - fildes[0] will be used to read from the data queue.
 * - fildes[1] will be used to write to the data queue.
```

```
*
* Note that whether you can write to fildes[0] or read from
* fildes[1] is undefined. */
int pipe(int fildes[2]);
```

- **int dup(int oldfd)** - creates an alias for the provided file descriptor and returns the new fd value. dup always uses the smallest available file descriptor. Thus, if we called dup first thing in our program, it would use file descriptor 3 (0, 1, and 2 are already signed to stdin, stdout, stderr). The old and new file descriptors refer to the same open file description and may be used interchangeably.
- **int dup2(int oldfd, int newfd)** - dup2 is a system call similar to dup. It duplicates the oldfd file descriptor, this time using newfd instead of the lowest available number. If newfd was open, it closed before being reused. This becomes very useful when attempting to redirect output, as it automatically takes care of closing the file descriptor, performing the redirection in one elegant command. For example, if you wanted to redirect standard output to a file, then you would simply call dup2, providing the open file descriptor for the file as the first command and 1 (standard output) as the second command.
- **signals** - A signal is a software interrupt, a way to communicate information to a process about the state of other processes, the operating system, and the hardware. A signal is an interrupt in the sense that it can change the flow of the program —when a signal is delivered to a process, the process will stop what its doing, either handle or ignore the signal, or in some cases terminate, depending on the signal.
- **int signal(int signum, void (*handler)(int))** - signal() is the primary system call for signal handling, which given a signal and function, will execute the function whenever the signal is delivered. This function is called the signal handler because it handles the signal.
- **SIG_IGN, SIG_DFL** Usually the second argument to signal takes a user defined handler for the signal. However, if you'd like your process to drop the signal you can use SIG_IGN. If you'd like your process to do the default behavior for the signal use SIG_DFL.

2 Files

2.1 Files vs File Descriptor

What's the difference between `fopen` and `open`?

2.2 Quick practice with write and seek

What will the `test.txt` file look like after I run this program? For simplicity assume `read()` and `write()` do not return short. (Hint: if you write at an offset past the end of file, the bytes inbetween the end of the file and the offset will be set to 0.)

```
int main() {
    char buffer[200];
    memset(buffer, 'a', 200);
    int fd = open("test.txt", O_CREAT|O_RDWR);
    write(fd, buffer, 200);
    lseek(fd, 0, SEEK_SET);
    read(fd, buffer, 100);
    lseek(fd, 500, SEEK_CUR);
    write(fd, buffer, 100);
}
```

2.3 Reading and Writing with File Pointers vs. Descriptors

Write a utility function, `void copy(const char *src, const char *dest)`, that simply copies the file contents from `src` and places it in `dest`. You can assume both files are already created. Also assume that the `src` file is at most 100 bytes long. First, use the file pointer library to implement this. Fill in the code given below:

```
void copy(const char *src, const char *dest) {
    char buffer [100];
    FILE* read_file = fopen(_____, ____);
    int buf_size = fread(_____, ____, _____, _____);
    fclose(read_file);

    FILE* write_file = fopen(_____, ____);
    fwrite(_____, ____, _____, _____);
    fclose(write_file);
}
```

Next, use file descriptors to implement the same thing.

```
void copy(const char *src, const char *dest) {
    char buffer [100];
    int read_fd = open(_____, _____);
    int bytes_read = 0;
    int buf_size = 0;

    while ((bytes_read = read(_____, _____, _____)) > 0) {
        _____
    }
    close(read_fd);

    int bytes_written = 0;
    int write_fd = open(_____, _____);
    while (_____) {
        _____ += write(_____, _____, _____);
    }
    close(write_fd);
}
```

Compare the file pointer implementation to the file descriptor implementation. In the file descriptor implementation, why does **read** and **write** need to be called in a loop?

3 Pipes

3.1 Basic Pipes

In the following code we use a pipe to communicate data between 2 file descriptors.

```
int main() {
    int fds[2];
    pipe(fds);
    int rfd = fds[0];
    int wfd = fds[1];
    char *str = "hello world";
    size_t bytes_written = 0;
    size_t total = 0;
    while (bytes_written = write(wfd, &str[total], strlen(&str[total]) + 1)) {
        total += bytes_written;
        if (str[total - 1] == '\0') break;
    }
    close(wfd);
    char *read_str = malloc(strlen(str) + 1);
    total = 0;
    size_t bytes_read;
    while (bytes_read = read(rfd, &read_str[total], 50)) {
        total += bytes_read;
    }
    printf("%s", read_str);
    return 0;
}
```

What would the code above print out?

3.2 Pipe and Fork

Now, we use pipes in order for 2 processes to share data between each other.

```
int main() {
    int fds[2];
    pipe(fds);
    pid_t child_pid = fork();
    size_t total = 0;
    char *str = "hello world";
    int rfd = fds[0];
    int wfd = fds[1];
    if (child_pid == 0) {
        size_t bytes_written = 0;
        while ((bytes_written = write(wfd, &str[total], strlen(&str[total]) + 1))) {
            total += bytes_written;
            if (str[total - 1] == '\0') break;
        }
    } else {
        close(wfd);
        char *read_buf = malloc(strlen(str) + 1);
        total = 0;
        size_t bytes_read;
        while ((bytes_read = read(rfd, &read_buf[total], 50))) {
            total += bytes_read;
        }
        printf("%s\n", read_buf);
    }
    return 0;
}
```

What would the code above print out?

4 Signals

The following is a list of standard Linux signals:

Signal	Value	Action	Comment
SIGHUP	1	Terminate	Hangup detected on controlling terminal or death of controlling process
SIGINT	2	Terminate	Interrupt from keyboard (Ctrl - c)
SIGQUIT	3	Core Dump	Quit from keyboard (Ctrl - \)
SIGILL	4	Core Dump	Illegal Instruction
SIGABRT	6	Core Dump	Abort signal from abort(3)
SIGFPE	8	Core Dump	Floating point exception
SIGKILL	9	Terminate	Kill signal
SIGSEGV	11	Core Dump	Invalid memory reference
SIGPIPE	13	Terminate	Broken pipe: write to pipe with no readers
SIGALRM	14	Terminate	Timer signal from alarm(2)
SIGTERM	15	Terminate	Termination signal
SIGUSR1	30,10,16	Terminate	User-defined signal 1
SIGUSR2	31,12,17	Terminate	User-defined signal 2
SIGCHLD	20,17,18	Ignore	Child stopped or terminated
SIGCONT	19,18,25	Continue	Continue if stopped
SIGSTOP	17,19,23	Stop	Stop process
SIGTSTP	18,20,24	Stop	Stop typed at tty
SIGTTIN	21,21,26	Stop	tty input for background process
SIGTTOU	22,22,27	Stop	tty output for background process

4.1 Signal Handlers

Assume you are running this program from a Bash shell. List all the ways you can cause this program to exit using signals.

```
#include <signal.h>
#include <stdio.h>
#include <unistd.h>
#include <stdlib.h>
void sigint_handler(int sig) {
    if (sig == SIGINT || sig == SIGQUIT) {
        exit(1);
    }
}
void sigint_handler_2(int sig) {
    if (sig == SIGINT) {
        signal(SIGINT, sigint_handler);
    }
}
int main() {
    signal(SIGINT, sigint_handler_2);
    signal(SIGQUIT, sigint_handler);
    while (1) {
        printf("Sleeping for a second (U.U)\n");
        sleep(1);
    }
}
```

5 Dup and Dup2

What does C print in the following code?

```
int main(int argc, char **argv)
{
    int pid, status;
    int newfd;
    if ((newfd = open("output_file.txt", O_CREAT|O_TRUNC|O_WRONLY, 0644)) < 0) {
        exit(1);
    }
    printf("The last digit of pi is...");
    fflush(stdout);
    dup2(newfd, 1);
    printf("five\n");
    exit(0);
}
```

6 Synchronization

6.1 Locking via Disabling Interrupts

Consider the following implementation of Locks:

```
Lock::Acquire() {                               Lock::Release() {
    disable_interrupts();                          enable_interrupts();
}                                                  }
```

1. For a single-processor system state whether this implementation is incorrect.

2. For a multiprocessor system, explain what additional reason(s) might make this implementation incorrect?